

# **EXPLORER 710**

High-Speed, Portable BGAN Terminal



## Raising the BGAN bar

EXPLORER 710 is a portable satellite terminal set to usher in a new era in the world of BGAN by setting new standards for size, speed and features.

# **Smallest and Lightest**

The smallest full Class 1 BGAN terminal positioned to support broadcasters by enhancing the quality of mobile outside broadcasting.



## **Specifications**

Dimensi	ons
Jillielisi	OHS

Total H / W / D: 332 / 279 / 54 mm 13.07 / 10.98 / 2.13 inches

Total weight: 3.5 kg / 7.7 lbs (incl. battery) Antenna: 1.9 kg / 4.2 lbs Transceiver (incl. battery): 1.6 kg / 3.5 lbs

## Global Services

4 kbps AMBE+2 Premium voice: 3.1 kHz audio, 64 kbps Standard IP: Up to 492 kbps Streaming IP: 32, 64, 128 kbps

(256 kbps & BGAN X-Stream) High Data Rate Streaming: Min. 600 kbps

Min. 300 kbps (Half-channel HDR) ISDN: UDI 64 kbps / RDI 56 kbps

SMS: Not supported

1518.0 - 1525.0 MHz (Rx) (EMEA) Inmarsat frequencies: 1525.0 - 1559.0 MHz (Rx)

1626.5 - 1660.5 MHz (Tx) 1668.0 - 1675.0 MHz (Tx) (FMFA)

EIRP: 20dBW ±1dB

User Interface: PMOLED Display, 5 navigation keys.

Audio and LCD pointing aids and LED

indicator, Compass

Languages: UK, FR, DE, ES, RU and CN

Approvals:

Inmarsat Class 1 Type Approval at launch CE & FCC at launch. Other approvals TBC





The first and only BGAN terminal to support the full High Data Rate on-demand streaming service from Inmarsat. With speeds averaging 650 kbps, the EXPLORER 710 sets a new standard for mobile video newsgathering.

Double the speed with Plug & Play bonding; simply connect two EXPLORER 710 terminals with an ethernet cable and achieve streaming rates over 1 Mbps.

#### Fastest ever BGAN

# **Smart and Easy**

EXPLORER 710 introduces smart devices to the world of BGAN, enabling users to connect their own smart phone for terminal control, voice calls and connectivity. The EXPLORER Connect App with a SIP softphone is available on Android and IOS.

Other features include a USB host interface, hot-swappable batteries, a large easy-to-use LED display and multiple interfaces to support a wide range of applications.

#### Interfaces

# 1 x Analogue RJ-11 phone/fax interfaces

### 2 x LAN (RJ-45) interface

PoE Cl. 2 on one RJ-45 interface Power over Ethernet: 100m / 328ft (Cat5 UTP) Max. cable length:

# 1 x USB host interface

2.0 (host), Charging up to 2A

#### 1 x ISDN interface

Connector type: RI-45

Max. units per port: 8, max. total power supplied 1W

# 1 x Transceiver / Antenna interface

Connector type: TNC-TNC Max. cable loss: 1.4 / 20dB @ 1.5GHz

# 1 x BGAN SIM-Card slots

# WLAN Access Point

Standard: IEEE 802.11 b/g

# **Environmental conditions**

## Temperature

Operational (ambient): -25°C to +55°C / -13°F to +131°F Storage (excl. battery): -40°C to +80°C / -40°F to +176°F

# Battery storage temperature

 $-20^{\circ}$ C to  $+60^{\circ}$ C /  $-4^{\circ}$ F to  $+140^{\circ}$ F 1 month: 3 months: -20°C to +45°C / -4°F to +113°F -20°C to +20°C / -4°F to +68°F 1 year:

Water and dust: Transceiver: IP52 / Antenna: IP66

Relative humidity: 95% non-condensing at +40°C / +104°F

# Power

DC input range: 10-32VDC

# Power consumption

Intelligent Power Management 65W (max.)

# AC/DC power supply

100-240VAC, 47-63Hz, 65W Input: 19VDC Output:

Connector type: 2.5 / 5.5 mm power jack

Battery: Lithium ion, rechargeable Stand-by time: 24 hours (to be confirmed) Transmit time, max.: 2h30m @ 144 kbps (25°C / 77°F) 1h30m @ 650 kbps 3h30m @ 492 kbps Receive time, max.:

Subject to change without further notice

#### Other features

Built-in SIP server

Embedded Webserver

Advanced Router with admin control

Wireless Access Point

Battery hot-swap and Built-in BGAN bonding Remote activation and remote management

#### **EXPLORER Connect App for IOS and Android:**

Includes a SIP Softphone, Terminal Access to control your BGAN and Pointing Assistance.

# **EXPLORER Cellular Modem for USB:**

With the EXPLORER LTE Modern you can connect local cellular networks and use the EXPLORER 510 as wireless router for all your devices.

# **Package**

EXPLORER 710 Transceiver & Antenna incl. rechargeable lithium ion battery, Antenna cable, 2m ISDN/LAN cable, 115/230VAC power supply, Quick start guide.

# Accessories

403720B-100 EXPLORER 710 Antenna 403686G Lithium Ion Battery 403720B-010 Battery Hot Swap Cable 403682P 100-240V AC/DC Power Supply 403650A-009 Car Charger Cable 403670A-00500 IP Handset incl. Cradle 403650A-921 Pole Mount Kit 403720B-942 10m Antenna Cable 403720B-945 30m Antenna Cable 403720B-947 50m Antenna Cable 403756A-0500 EXPLORER Cellular USB Modem

# Product number

EXPLORER 710 Terminal 403720B-00500

Arycom USA LLC 575 Pharr Rd NE - Unit # 11703 Atlanta, GA 30355-6000 P. +1 404 920 4620

Arycom Brasil Av. Nove de Julho, 3228 - cj. 910 Id. Paulista 01406-000 São Paulo - SP /Brazil P. +55 11 3051 3001